

Back referencing from bibliographical citations^{*}

David Carlisle and Sebastian Rahtz (deceased)[†]

2025-06-21

Documentation overview for `hyperref`

The documentation for package `hyperref` consists of several files:

[Manual](#) The **USER MANUAL** (also available as HTML).

[ChangeLog](#) This file records the version history.

[Bookmark talk, slides](#) Slides for the talk “PDF information and navigation elements with `hyperref`, `pdfTeX` and `thmbpdf`” at EuroTeX 1999.

[Bookmark talk, paper](#) The paper version of the talk.

Source code documentation:

[hyperref.dtx](#) This is the source code documentation for `hyperref`.

 [backref.dtx](#) “Back referencing from bibliographical citations” (this file)

[nameref.dtx](#) “Section name references in `LATEX`”

Contents

1	Introduction	2
2	Usage	2
2.1	Options	2
2.1.1	Options for type of back references	2
2.1.2	Language options	3
2.1.3	Other options	3
2.2	Detecting the end of a bibliography entry	3
2.3	Formatting of the back references list	4
2.3.1	Formatting hook <code>\backref</code>	4
2.3.2	Formatting hook <code>\backrefalt</code>	4
2.3.3	Refinement <code>\backrefentrycount</code>	5

^{*}This file has version number v1.45, last revised 2025-06-21.

[†]<https://github.com/latex3/hyperref/issues>

3	The macros	5
3.1	Package identification	5
3.2	Options	5
3.2.1	Option verbose	5
3.2.2	Options for way of working	6
3.2.3	Language options	6
3.2.4	Process options	8
3.3	The bibliography	9
3.4	Reading .brf file	10
3.5	Initialization	14
3.6	Collecting back cite information	15
3.7	Rerun warning	15
4	Index	16

1 Introduction

2 Usage

2.1 Options

The supported options are given as package options. Few options (e.g. `verbose`, `enable`, `disable`) can be changed after the package is loaded by the macro `\backrefsetup`, e.g.:

```
\usepackage[verbose]{backref}
\backrefsetup{verbose=false}
```

This macro is available since version 2012/07/24 v1.37.

2.1.1 Options for type of back references

In short the following options set the type of back references. Default is option `pageref`.

<code>ref</code>	section number
<code>pageref</code>	page number
<code>hyperref</code>	section number as hyper link
<code>hyperpageref</code>	page number as hyper link

The options that start with `hyper` are intended for the use with package `hyperref`. In this case package `backref` will be loaded automatically if the `hyperref` options `backref` or `pagebackref` are given. Package `hyperref` then loads package `backref` with the appropriate option:

hyperref option	backref option set by hyperref
<code>backref</code>	<code>hyperref</code>
<code>backref=section</code>	<code>hyperref</code>
<code>backref=slide</code>	<code>hyperref</code>
<code>backref=page</code>	<code>hyperpageref</code>
<code>pagebackref</code>	<code>hyperpageref</code>

2.1.2 Language options

Currently supported options are `english` (`american`, `australian`, `british`, `canadian`, `newzealand`, `UKenglish`, `USenglish`), `german` (`ngerman`, `austrian`, `naustrian`), `french` (`acadian`, `canadien`, `frenchb`, `francais`), `spanish`, and `brazil` (`brazilian`). Default is `english`.

2.1.3 Other options

verbose: A message is written into the `.aux` file for each reference that is found for back citing.

enable, disable: If a citation should not be back cited, then the recording can be turned off by option `disable` and enabled again afterwards, e.g.:

```
\backrefsetup{disable}\cite{...}\backrefsetup{enable}
or
\backrefsetup{disable}\listoffigures \backrefsetup{enable}
```

Both options are added in version 2012/07/24 v1.37.

2.2 Detecting the end of a bibliography entry

Package `backref` has to be able to detect the end of an entry in the bibliography, therefore each `\bibitem` entry must be ended by an empty line (or a `\par` token).

Example:

```
\begin{thebibliography}{9}
\bibitem[bib:abc] First entry.

\bibitem[bib:foo] Second entry.

\end{thebibliography}
```

Then package `backref` can automatically add hooks for the back references list at the end of the entries.

`\backrefparscanfalse` Sometimes it is not appropriate if the entry is read as argument. For example, catcode changes for verbatim stuff do not have the desired effect. Therefore the scan for the `\par` token can be disabled by `\backrefparscanfalse` before `\bibitem` and enabled by `\backrefparscantrue` afterwards.

`\backrefprint` If the scan for the end of the entry is disabled, then package `backref` does not know where to put the back references list. The list is printed by the macro `\backrefprint`, thus just call it at the right place. Example:

```
\backrefparscanfalse % disable scan for entry ending
\bibitem[...]{...}
... \verb|...| ... % potentially dangerous stuff
... \url{...} ...
\backrefprint         % print back reference list here
\backrefparscantrue  % enable scan again
```

2.3 Formatting of the back references list

The back references list is separated from the entry by `\newblock`, if the used bibliography package supports this. The package options control the kind of back references (page numbers, sections numbers), whereas the hooks control the formatting.

There are two hooks `\backref` and a new hook `\backrefalt`, available since version 1.21 of package `backref`. The former one is enabled by default.

2.3.1 Formatting hook `\backref`

Macro `\backref` has a comma separated list of backref references as first and only argument. With `hyperref` options only this list will be printed. Without `hyperref` there is an introductory text, controlled by macros `\backrefpagesname` or `\backrefsectionsname`.

2.3.2 Formatting hook `\backrefalt`

`\backrefalt` is a new interface since version 1.21 of package `backref`. It takes four arguments:

1. Number of citations without dupes.
2. Back references list without dupes.
3. Number of all citations (with dupes).
4. Back reference list with all entries (with dupes).

The latter options consider equal entries as one entry. Now `\backrefalt` can easily be defined with text that depends on the number of citations, for example:

```
\usepackage[backref]{backref}
\renewcommand*{\backref}[1]{}% for backref < 1.33 necessary
\renewcommand*{\backrefalt}[4]{%
  \ifcase #1 %
    No citations.%
  \or
    One citation in section #2.%
  \else
    #1 citations in sections #2.%
  \fi
}
```

The separation between the list entries are controlled by the following macros:

- `\backrefsep`: inserted between entries except for the next cases, default is “`,□`”.
- `\backreftwosep`: inserted between entries in a list of two entries, default is “`□and~`”.
- `\backreflastsep`: inserted between the last two entries of a list with more than two entries, default is “`,□and~`”.

Examples:

```

\langle entry1 \rangle
\langle entry1 \rangle \backref{two}sep \langle entry2 \rangle
\langle entry1 \rangle \backref{sep} \langle entry2 \rangle \backref{last}sep \langle entry3 \rangle

```

Since version 1.33 it is not necessary to redefine `\backref`, it is automatically disabled if defined.

2.3.3 Refinement `\backrefentrycount`

Since version 1.33 the entries of the distinct list of interface `\backrefalt` are wrapped in `\backrefentrycount`. The macro is called with two arguments. The first is the backref entry and the second one the citation count of this entry. As default the macro passes the first argument through and ignores the count argument. But it can be redefined, e.g.

```

\renewcommand*\backrefalt}[4]{...}% see above
\renewcommand*\backrefentrycount}[2]{%
  #1%
  \ifnum#2>1 %
    ~(#2)%
  \fi
}

```

In case of duplicates, the distinct entry is appended by the number of citations in parentheses.

3 The macros

Internal command names of this package start with `\BR@`, commands, that store the original meaning of commands, which will be redefined, are prefixed with `\BRorg@`.

3.1 Package identification

```
1 \package{}
```

3.2 Options

```

2 \RequirePackage{kvoptions}[2011/06/30]
3 \RequirePackage{kvsetkeys}[2009/07/30]
4 \SetupKeyvalOptions{%
5   family=backref,%
6   prefix=BR@,%
7 }

```

```
\backrefsetup
```

```
8 \newcommand*\backrefsetup{\kvsetkeys{backref}}
```

3.2.1 Option verbose

If package `hyperref` is loaded, then its setting is used as default for the verbose switch.

```
9 \DeclareBoolOption[
```

```

10 \ifundefined{ifHy@verbose}{%
11   false%
12 }{%
13   \ifx\ifHy@verbose\iftrue true\else false\fi
14 }%
15 ]{verbose}

```

3.2.2 Options for way of working

What is printed depends on how the 3 available items of information are used (page number, section number, label).

```

16 \long\def\page@backref#1#2#3{#1}
17 \long\def\section@backref#1#2#3{#2}
18 \long\def\hyper@section@backref#1#2#3{\hyperlink{#3}{#2}}
19 \long\def\hyper@page@backref#1#2#3{\hyperlink{page.#1}{#1}}

```

Now the options follows, that can be used without package hyperref.

```

20 \DeclareVoidOption{pageref}{%
21   \def\backref{\backrefpagesname\ }%
22   \let\backrefxxx\page@backref
23 }
24 \DeclareVoidOption{ref}{%
25   \def\backref{\backrefsectionsname\ }%
26   \let\backrefxxx\section@backref
27 }

```

Set up back-referencing to be hyper links, by page or section.

```

28 \DeclareVoidOption{hyperref}{%
29   \def\backref{\let\backrefxxx\hyper@section@backref
30 }
31 \DeclareVoidOption{hyperpageref}{%
32   \def\backref{\let\backrefxxx\hyper@page@backref
33 }

```

Recording the back references in the auxiliary file can be enabled and disabled by the following options.

```

34 \DeclareBoolOption[true]{enable}
35 \DeclareComplementaryOption{disable}{enable}

```

3.2.3 Language options

```

36 \def\backrefenglish{%
37   \def\backrefpagesname{pages}%
38   \def\backrefsectionsname{sections}%
39   \def\backrefsep{, }%
40   \def\backreftwosep{ and~}%
41   \def\backreflastsep{, and~}%
42 }
43 \def\backrefgerman{%
44   \def\backrefpagesname{Seiten}%
45   \def\backrefsectionsname{Abschnitte}%
46   \def\backrefsep{, }%
47   \def\backreftwosep{ und~}%
48   \def\backreflastsep{ und~}%
49 }

```

```

50 \def\backreffrench{%
51   \def\backrefpagesname{pages}%
52   \def\backrefsectionsname{sections}%
53   \def\backrefsep{, }%
54   \def\backreftwosep{ et~}%
55   \def\backreflastsep{ et~}%
56 }
57 \def\backrefspanish{%
58   \def\backrefpagesname{p\'aginas}%
59   \def\backrefsectionsname{secciones}%
60   \def\backrefsep{, }%
61   \def\backreftwosep{ y~}%
62   \def\backreflastsep{ y~}%
63 }
64 \def\backrefbrazil{%
65   \def\backrefpagesname{p\'aginas}%
66   \def\backrefsectionsname{secc\c oes}%
67   \def\backrefsep{, }%
68   \def\backreftwosep{ e~}%
69   \def\backreflastsep{ e~}%
70 }
71 \def\backrefafrikaans{%
72   \def\backrefpagesname{bladsye}%
73   \def\backrefsectionsname{afdelings}%
74   \def\backrefsep{, }%
75   \def\backreftwosep{ en~}%
76   \def\backreflastsep{ en~}%
77 }
78 \def\backrefitalian{%
79   \def\backrefpagesname{pagine}%
80   \def\backrefsectionsname{sezioni}%
81   \def\backrefsep{, }%
82   \def\backreftwosep{ e~}%
83   \def\backreflastsep{ e~}%
84 }%

```

Instead of package babel's definition of \addto the implementation of package varioref is used. Additionally argument #1 is checked for \relax.

```

85 \def\BR@addto#1#2{%
86   #2%
87   \@temptokena{#2}%
88   \ifx#1\relax
89     \let#1\@empty
90   \fi
91   \ifx#1\@undefined
92     \edef#1{\the\@temptokena}%
93   \else
94     \toks@\expandafter{#1}%
95     \edef#1{\the\toks@\the\@temptokena}%
96   \fi
97   \@temptokena{}\toks@\@temptokena
98 }
99 \def\BR@DeclareLang#1#2{%
100   \begingroup

```

```

101 \edef\x##1##2{%
102 \noexpand\ifx##2\relax
103 \errmessage{No definitions for language `#2' found!}%
104 \noexpand\fi
105 \endgroup
106 \noexpand\DeclareVoidOption{#1}{%
107 \noexpand\BR@addto{\noexpand##1}{\noexpand##2}%
108 }%
109 }%
110 \expandafter\x\csname extras#1\expandafter\endcsname
111 \csname backref#2\expandafter\endcsname
112 }
113 \BR@DeclareLang{english}{english}
114 \BR@DeclareLang{american}{english}
115 \BR@DeclareLang{australian}{english}
116 \BR@DeclareLang{british}{english}
117 \BR@DeclareLang{canadian}{english}
118 \BR@DeclareLang{newzealand}{english}
119 \BR@DeclareLang{UKenglish}{english}
120 \BR@DeclareLang{USenglish}{english}
121 \BR@DeclareLang{german}{german}
122 \BR@DeclareLang{ngerman}{german}
123 \BR@DeclareLang{austrian}{german}
124 \BR@DeclareLang{naustrian}{german}
125 \BR@DeclareLang{french}{french}
126 \BR@DeclareLang{acadian}{french}
127 \BR@DeclareLang{canadien}{french}
128 \BR@DeclareLang{frenchb}{french}
129 \BR@DeclareLang{français}{french}
130 \BR@DeclareLang{spanish}{spanish}
131 \BR@DeclareLang{brazil}{brazil}
132 \BR@DeclareLang{brazilian}{brazil}
133 \BR@DeclareLang{afrikaans}{afrikaans}
134 \BR@DeclareLang{italian}{italian}

```

Default is the english version:

```
135 \backrefenglish
```

3.2.4 Process options

```
136 \backrefsetup{pageref}
137 \ProcessKeyvalOptions*
```

\BR@DisableOption

```

138 \def\BR@DisableOption#1{%
139 \DisableKeyvalOption[%
140 action=warning,%
141 package=backref,%
142 ]{backref}{#1}%
143 }

144 \BR@DisableOption{ref}
145 \BR@DisableOption{pageref}
146 \BR@DisableOption{hyperref}
147 \BR@DisableOption{hyperpageref}

```


3.3 The bibliography

```

\ifbackrefparscan
148 \newif\ifbackrefparscan
149 \backrefparscantrue

\ifBR@BackrefAlt
150 \newif\ifBR@BackrefAlt

\BR@bibitem
151 \def\BR@bibitem{%
152   \ifbackrefparscan
153     \expandafter\@ifnextchar\expandafter[\expandafter
154     \BR@@lbibitem\expandafter\BR@@bibitem
155   \else
156     \expandafter\@ifnextchar\expandafter[\expandafter
157     \BR@@@lbibitem\expandafter\BR@@@bibitem
158   \fi
159 }

160 \def\BR@@lbibitem[#1]#2#3\par{%
161   \let\backrefprint\BR@backrefprint
162   \BRorg@bibitem[#{1}]{#2}#3%
163   \BR@backref{#2}%
164 }%
165 \def\BR@@@bibitem#1#2\par{%
166   \let\backrefprint\BR@backrefprint
167   \BRorg@bibitem{#1}#2%
168   \BR@backref{#1}%
169 }
170 \def\BR@@@lbibitem[#1]#2{%
171   \def\backrefprint{\BR@backref{#2}}%
172   \BRorg@bibitem[#{1}]{#2}%
173 }
174 \def\BR@@@bibitem#1{%
175   \def\backrefprint{\BR@backref{#1}}%
176   \BRorg@bibitem{#1}%
177 }
178 \def\BR@backrefprint{%
179   \PackageError{backref}{%
180     \string\backrefprint\space is only available after \string\bibitem
181     \MessageBreak
182     with setting \string\backrefparscanfalse
183   }\@ehc
184 }
185 \let\backrefprint\BR@backrefprint
186 \def\BR@backref#1{%
187   \newblock
188   \begingroup
189     \csname @safe@activetrue\endcsname
190     \expandafter\providecommand\csname brc@#1\endcsname{0}%
191     \expandafter\providecommand\csname brcd@#1\endcsname{0}%
192     \csname @safe@activesfalse\endcsname\expandafter\endcsname
193   \ifBR@BackrefAlt

```

```

194 \ifx\backrefentrycount\BR@BackrefEntryCountUnused
195 \else
196 \BR@PopulateEntryCount{#1}%
197 \fi
198 \expandafter\backrefalt\csname br@#1\expandafter\endcsname
199 \csname brl@#1\expandafter\endcsname
200 \csname brcd@#1\expandafter\endcsname
201 \csname brld@#1\endcsname
202 \else
203 \expandafter\backref\csname br@#1\expandafter\endcsname
204 \fi
205 \endgroup
206 \par
207 }
208 \ifundefined{newblock}{\def\newblock{\par}}{}
209 \let\BR@Unused\@empty
210 \def\BR@BackrefAltUnused#1#2#3#4{\BR@Unused}
211 \ifundefined{backrefalt}{%
212 \let\backrefalt\BR@BackrefAltUnused
213 }{}
214 \def\BR@BackrefEntryCountUnused#1#2{\BR@Unused#1}
215 \ifundefined{backrefentrycount}{%
216 \let\backrefentrycount\BR@BackrefEntryCountUnused
217 }{}

```

3.4 Reading .brf file

`\backcite` The file `\jobname.brf` collects the back cite information as calls of `\backcite` with the information in the arguments.

The first argument of macro `\backcite` is the citation label, the second parameter contains the page number (`\thepage`), the current label of the citation (`\@currentlabel`), and the current anchor name (`\@currentHref`). Example for a citation at the first page in second section:

```
\backcite {bib:abc}{1}{2}{section.2}
```

While the file `\jobname.brf` is read, the information are collected and stored in macros whose names are built by the citation label *<label>*:

<code>\br@<label></code>	list, entries separated by comma without dupes
<code>\brc@<label></code>	number of citations without dupes
<code>\brl@<label></code>	backref list without dupes
<code>\brcd@<label></code>	number of all citations (with dupes)
<code>\brld@<label></code>	backref list with all entries (with dupes)

What are “dupes”? An instance: you have three references to an entry in the bibliography on the first page:

```

\backcite {bib:abc}{1}{1}{section.1}
\backcite {bib:abc}{1}{1}{section.1}
\backcite {bib:abc}{1}{2}{section.2}

```

Then the whole backref list with option `pageref` would print, e.g.:

Entry for `bib:abc`. Cited on pages 1, 1, 1.

Without dupes the entries with the same page number would be removed, e.g.:

Entry for `bib:abc`. Cited on page 1.

Also the third entry is removed, because it has the same page number. For the comparison only these pieces of information are considered that will be used later by `\backrefxxx`. With option `pageref` macro `\backrefxxx` becomes `\page@backref` that throws away the second and third argument and only uses the first argument with the page number. To be more precise, the first expansion of `\backrefxxx` is used in comparison. If some arguments are used here, but later omitted, then this will not be detected.

`\backrefxxxdupe` With option `hyperref` you will get two entries in the following example because the second entry differs in the link information, so the result will be the same section number, but as different links.

```
\backref {bib:abc}{1}{1}{section.1}
\backref {bib:abc}{1}{1}{equation.1}
```

Macro `\backrefxxxdupe` will be used in the comparison test if it is defined. Thus you can provide a definition in this case as follows:

```
\newcommand*{\backrefxxxdupe}[3]{#2}
```

Then only the section number is interpreted, but not the anchor name.

To avoid same entries, it is checked before, whether the entry already exists. Only the information needed by `\backrefxxx` is compared.

```
218 \def\backcite#1#2{%
219   \@for\x:=#1\do{%
220     \begingroup
221       \csname @safe@activetrue\endcsname
222       \edef\x{\endgroup
223         \def\noexpand\x{\expandafter\@firstofone\x\@empty}}%
224       }%
225     \x
```

Now macro `\x` contains the citation label name.

```
226   \expandafter\ifx\csname br@\x\endcsname\relax
```

Initialization, fill in the first entry.

```
227     \expandafter\protected@xdef\csname br@\x\endcsname{%
228       \protect\backrefxxx#2%
229     }%
230     \ifBR@BackrefAlt
231       \global\expandafter\let\csname brl@\x\expandafter\endcsname
232         \csname br@\x\endcsname
233       \global\expandafter\let\csname brld@\x\expandafter\endcsname
234         \csname br@\x\endcsname
235       \expandafter\gdef\csname brc@\x\endcsname{1}%
236       \expandafter\gdef\csname brcd@\x\endcsname{1}%
237     \fi
238   \else
```

Fill in further entry. But check for dupe first.

```

239 \begingroup
240 \ifundefined{backrefxxdupe}{-}{\let\backrefxxx\backrefxxdupe}%
241 \expandafter\def\expandafter\reserved@a\expandafter{%
242 \backrefxxx#2%
243 }%
244 \let\BRorg@backrefxxx\backrefxxx
245 \global\let\BR@found=N%
246 \long\def\backrefxxx##1##2##3{%
247 \expandafter\def\expandafter\reserved@b\expandafter{%
248 \BRorg@backrefxxx{##1}{##2}{##3}%
249 }%
250 \ifx\reserved@a\reserved@b
251 \global\let\BR@found=Y%
252 \fi
253 }%
254 \setbox\@tempboxa\hbox{\csname br@\x\endcsname}%
255 \endgroup
256 \let\backrefsep\relax
257 \def\backreftwosep{\backrefsep}%
258 \def\backreflastsep{\backrefsep}%
259 \if N\BR@found
260 \expandafter\protected@xdef\csname br@\x\endcsname{%
261 \csname br@\x\endcsname, %
262 \protect\backrefxxx#2%
263 }%
264 \ifBR@BackrefAlt
265 \expandafter\protected@xdef\csname brl@\x\endcsname{%
266 \csname brl@\x\endcsname
267 \ifnum\@nameuse{brc@\x}=1 %
268 \noexpand\backreftwosep
269 \else
270 \noexpand\backreflastsep
271 \fi
272 \protect\backrefxxx#2%
273 }%
274 \count@=\@nameuse{brc@\x}\relax
275 \advance\count@ by 1 %
276 \expandafter\xdef\csname brc@\x\endcsname{\the\count@}%
277 \fi
278 \fi
279 \ifBR@BackrefAlt
280 \expandafter\protected@xdef\csname brld@\x\endcsname{%
281 \csname brld@\x\endcsname
282 \ifnum\@nameuse{brcd@\x}=1 %
283 \noexpand\backreftwosep
284 \else
285 \noexpand\backreflastsep
286 \fi
287 \protect\backrefxxx#2%
288 }%
289 \count@=\@nameuse{brcd@\x}\relax
290 \advance\count@ by 1 %
291 \expandafter\xdef\csname brcd@\x\endcsname{\the\count@}%

```

```

292     \fi
293     \fi
294 }%
295 }

```

\BR@PopulateEntryCount

```

296 \def\BR@PopulateEntryCount#1{%
297   \begingroup
298   \toks@{}%
299   \def\backrefsep{%
300     \toks@\expandafter{\the\toks@\backrefsep}%
301   }%
302   \def\backreftwosep{%
303     \toks@\expandafter{\the\toks@\backreftwosep}%
304   }%
305   \def\backreflastsep{%
306     \toks@\expandafter{\the\toks@\backreflastsep}%
307   }%
308   \def\protect{}%
309   \let\BR@backrefxxx\backrefxxx
310   \let\backrefxxx\BR@PopulateBackrefxxx
311   \def\BR@name{#1}%
312   \csname brl@#1\endcsname
313   \expandafter\xdef\csname brl@#1\endcsname{\the\toks@}%
314   \endgroup
315 }

```

\BR@PopulateBackrefxxx

```

316 \def\BR@PopulateBackrefxxx#1#2#3{%
317   \expandafter\def\expandafter\BR@tempa\expandafter{%
318     \BR@backrefxxx{#1}{#2}{#3}%
319   }%
320   \begingroup
321   \count@=\z@
322   \def\backrefsep{}%
323   \def\backreftwosep{}%
324   \def\backreflastsep{}%
325   \let\backrefxxx\BR@PopulateBackrefxxx
326   \csname brld@\BR@name\endcsname
327   \toks\tw@={\backrefxxx{#1}{#2}{#3}}%
328   \edef\x{\endgroup
329     \toks@{%
330       \the\toks@
331       \noexpand\backrefentrycount{%
332         \the\toks\tw@
333       }\the\count@}%
334     }%
335   }%
336   \x
337 }

```

\BR@@PopulateBackrefxxx

```

338 \def\BR@@PopulateBackrefxxx#1#2#3{%
339   \expandafter\def\expandafter\BR@tempb\expandafter{%

```

```

340 \BR@backrefxxx{#1}{#2}{#3}%
341 }%
342 \ifx\BR@tempa\BR@tempb
343 \advance\count@ \@ne
344 \fi
345 }

```

3.5 Initialization

```

346 \def\@currentHref{}
347 \AtBeginDocument{%
348 \let\BRorg@bibitem\bibitem
349 \let\bibitem\BR@bibitem
350 \let\BRorg@thebibliography\thebibliography
351 \def\thebibliography{%
352 \BR@starttoc
353 \BRorg@thebibliography
354 }%
355 \@ifundefined{NAT@parse}{%
356 \global\let\BRorg@citex\@citex
357 \global\let\@citex\BR@citex
358 }{%
359 \@ifpackageloaded{hyperref}{%}{%
360 \def\hyper@natlinkstart#1{\Hy@backout{#1}}%
361 }%
362 \PackageInfo{backref}{** backref set up for natbib **}%
363 }%
364 }

\BR@starttoc

365 \def\BR@starttoc{%
366 \ifx\backrefalt\BR@BackrefAltUnused
367 \global\BR@BackrefAltfalse
368 \else
369 \global\BR@BackrefAlttrue
370 \fi
371 \begingroup
372 \makeatletter
373 \@input{\jobname.brf}%
374 \if@filesw
375 \@ifundefined{tf@brf}{%
376 \expandafter\newwrite\csname tf@brf\endcsname
377 }{}%
378 \@ifundefined{tf@brf@open}{%
379 \BR@RerunFileCheck
380 \immediate\openout\csname tf@brf\endcsname\jobname.brf\relax
381 \gdef\tf@brf@open{%
382 }{}%
383 \fi
384 \@nobeckfalse
385 \endgroup
386 }

```

3.6 Collecting back cite information

```

\BR@citex
387 \def\BR@citex[#1]#2{%
388   \BRorg@citex[{#1}]{#2}%
389   \Hy@backout{#2}%
390 }

Grr. for chicago.sty
391 \@ifpackageloaded{chicago}{%
392   \let\BRorg@citedatax\@citedatax
393   \def\@citedatax[#1]#2{%
394     \BRorg@citedatax[{#1}]{#2}%
395     \Hy@backout{#2}%
396   }%
397 }{}

\Hy@backout
398 \def\Hy@backout#1{%
399   \@bsphack
400   \ifBR@enable
401     \ifBR@verbose
402       \PackageInfo{backref}{Back cite \string`#1\string'}%
403     \fi
404     \ifx\@empty\@currentlabel
405       \protected@write\@auxout{}{%
406         \string\writefile{brf}{%
407           \string\backcite{#1}{\thepage}{(document)}{Doc-Start}}%
408       }%
409     }%
410   \else
411     \protected@write\@auxout{}{%
412       \string\writefile{brf}{%
413         \string\backcite{#1}{\thepage}{\@currentlabel}{\@currentHref}}%
414       }%
415     }%
416   \fi
417 \else
418   \ifBR@verbose
419     \PackageInfo{backref}{Disabled back cite \string`#1\string'}%
420   \fi
421 \fi
422 \@esphack
423 }

```

3.7 Rerun warning

`\BR@RerunFileCheck` The following code computes a MD5 sum and the file size of the `.brf` file at the begin and the end of the document and compares them. A rerun warning is given, if they do not match. This method requires pdfTeX or LuaTeX. The method fails, if the MD5 sum and the file size are the same for a changed `.brf` file (it's probably very seldom).

```

424 \RequirePackage{rerunfilecheck}[2009/12/10]

```

```

425 \def\BR@RerunFileCheck{%
426   \RerunFileCheck{\jobname.brf}{%
427     \@ifundefined{tf@brf@open}{%
428       {%
429         \immediate\closeout{tf@brf
430       }%
431     }{%
432       Rerun to get bibliographical references right%
433     }%
434 }

435 \</package>

```

4 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in **roman** refer to the code lines where the entry is used.

Symbols	\AtBeginDocument .. 347	74, 81, 256, 257, 258, 299, 300, 322
\' 58, 65	B	
\@auxout 405, 411	\backrefsetup ... 8, 136	
\@bsphack 399	\backcite . 218, 407, 413	\backrefspanish 57
\@citedatax .. 392, 393	\backref 21, 25, 29, 32, 203	\backreftwosep .. 40,
\@citex 356, 357	\backrefafrikaans .. 71	47, 54, 61, 68,
\@currentHref . 346, 413	\backrefalt 198, 212, 366	75, 82, 257, 268,
\@currentlabel 404, 413	\backrefbrazil 64	283, 302, 303, 323
\@ehc 183	\backrefenglish 36, 135	\backrefxxx . 22, 26,
\@empty 89, 209, 223, 404	\backrefentrycount	29, 32, 228, 240,
\@esphack 422 194, 216, 331	242, 244, 246,
\@firstofone 223	\backreffrench 50	262, 272, 287,
\@for 219	\backrefgerman 43	309, 310, 325, 327
\@ifnextchar . 153, 156	\backrefitalian 78	\backrefxxxdupe 218, 240
\@ifpackageloaded .	\backreflastsep . 41,	\begingroup 100, 188, 220,
..... 359, 391	48, 55, 62, 69,	239, 297, 320, 371
\@ifundefined 10, 208,	76, 83, 258, 270,	\bibitem .. 180, 348, 349
211, 215, 240,	285, 305, 306, 324	\BR@@@bibitem . 157, 174
355, 375, 378, 427	\backrefpagesname .	\BR@@@lbibitem 157, 170
\@input 373 21, 37, 44,	\BR@@bibitem . 154, 165
\@nameuse 51, 58, 65, 72, 79	\backrefparscanfalse	\BR@@lbibitem . 154, 160
. 267, 274, 282, 289 3, 182	\BR@@PopulateBackrefxxx
\@ne 343	\backrefparscantrue 325, 338
\@nobreakfalse 384 3, 149	\BR@addto 85, 107
\@tempboxa 254	\backrefprint 168, 171, 175, 186	\BR@backref ... 163,
\@temptokena 87, 92, 95, 97	... 3, 161, 166,	171, 175, 186
\@undefined 91	171, 175, 180, 185	\BR@BackrefAltfalse 367
\@writefile .. 406, 412	\backrefsectionsname	\BR@BackrefAlttrue 369
_ 21, 25 25, 38, 45,	\BR@BackrefAltUnused
\~ 66	52, 59, 66, 73, 80 210, 212, 366
A	\backrefsep 39,	\BR@BackrefEntryCountUnused
\advance .. 275, 290, 343	46, 53, 60, 67, 194, 214, 216

<code>\BR@backrefprint ..</code>	281, 291, 312,	281, 291, 312,
. 161, 166, 178, 185	313, 326, 376, 380	313, 326, 376, 380
<code>\BR@backrefxxx</code>		<code>\endgroup</code>
.... 309, 318, 340	D	. 105, 205, 222,
<code>\BR@bibitem .. 151, 349</code>	<code>\DeclareBoolOption 9, 34</code>	255, 314, 328, 385
<code>\BR@citex 357, 387</code>	<code>\DeclareComplementaryOption</code>	<code>\errmessage</code> 103
<code>\BR@DeclareLang . 99,</code> 35	<code>\expandafter ... 94,</code>
113, 114, 115,	<code>\DeclareVoidOption</code>	110, 111, 153,
116, 117, 118,	20, 24, 28, 31, 106	154, 156, 157,
119, 120, 121,	<code>\def 16, 17, 18, 19, 21,</code>	190, 191, 192,
122, 123, 124,	25, 29, 32, 36,	198, 199, 200,
125, 126, 127,	37, 38, 39, 40,	203, 223, 226,
128, 129, 130,	41, 43, 44, 45,	227, 231, 233,
131, 132, 133, 134	46, 47, 48, 50,	235, 236, 241,
<code>\BR@DisableOption .</code>	51, 52, 53, 54,	247, 260, 265,
..... 138,	55, 57, 58, 59,	276, 280, 291,
144, 145, 146, 147	60, 61, 62, 64,	300, 303, 306,
<code>\BR@found . 245, 251, 259</code>	65, 66, 67, 68,	313, 317, 339, 376
<code>\BR@name 311, 326</code>	69, 71, 72, 73,	
<code>\BR@PopulateBackrefxxx</code>	74, 75, 76, 78,	F
..... 310, 316	79, 80, 81, 82,	<code>\fi 13, 90, 96,</code>
<code>\BR@PopulateEntryCount</code>	83, 85, 99, 138,	104, 158, 197,
..... 196, 296	151, 160, 165,	204, 237, 252,
<code>\BR@RerunFileCheck</code>	170, 171, 174,	271, 277, 278,
..... 379, 424	175, 178, 186,	286, 292, 293,
<code>\BR@starttoc . 352, 365</code>	208, 210, 214,	344, 370, 383,
<code>\BR@tempa 317, 342</code>	218, 223, 241,	403, 416, 420, 421
<code>\BR@tempb 339, 342</code>	246, 247, 257,	
<code>\BR@Unused 209, 210, 214</code>	258, 296, 299,	G
<code>\BRorg@backrefxxx .</code>	302, 305, 308,	<code>\gdef 235, 236, 381</code>
..... 244, 248	311, 316, 317,	<code>\global 231,</code>
<code>\BRorg@bibitem . 162,</code>	322, 323, 324,	233, 245, 251,
167, 172, 176, 348	338, 339, 346,	356, 357, 367, 369
<code>\BRorg@citedatax ..</code>	351, 360, 365,	
..... 392, 394	387, 393, 398, 425	H
<code>\BRorg@citex . 356, 388</code>	<code>\DisableKeyvalOption</code>	<code>\hbox 254</code>
<code>\BRorg@thebibliography</code> 139	<code>\Hy@backout</code>
..... 350, 353	<code>\do 219</code>	. 360, 389, 395, 398
		<code>\hyper@natlinkstart 360</code>
		<code>\hyper@page@backref</code>
	 19, 32
		<code>\hyper@section@backref</code>
	 18, 29
		<code>\hyperlink 18, 19</code>
C	E	I
<code>\c 66</code>	<code>\edef 92, 95, 101, 222, 328</code>	<code>\if 259</code>
<code>\closeout 429</code>	<code>\else 13, 93, 155, 195,</code>	<code>\if@filesw 374</code>
<code>\count@ ... 274, 275,</code>	202, 238, 269,	<code>\ifbackrefparscan .</code>
276, 289, 290,	284, 368, 410, 417 148, 152
291, 321, 333, 343	<code>\endcsname</code>	<code>\ifBR@BackrefAlt 150,</code>
<code>\csname 110, 111, 189,</code>	. 110, 111, 189,	193, 230, 264, 279
190, 191, 192,	190, 191, 192,	<code>\ifBR@enable 400</code>
198, 199, 200,	198, 199, 200,	<code>\ifBR@verbose . 401, 418</code>
201, 203, 221,	201, 203, 221,	<code>\ifHy@verbose 13</code>
226, 227, 231,	226, 227, 231,	
232, 233, 234,	232, 233, 234,	
235, 236, 254,	235, 236, 254,	
260, 261, 265,	260, 261, 265,	
266, 276, 280,	266, 276, 280,	

\ifnum	267, 282	107, 223, 268,	\space	180
\iftrue	13	270, 283, 285, 331	\string	180,
\ifx	13, 88, 91,		182, 402, 406,	
	102, 194, 226,	O	407, 412, 413, 419	
	250, 342, 366, 404	\openout		380
\immediate . . .	380, 429		T	
	J	P	\tf@brf	429
\jobname . .	373, 380, 426	\PackageError	\tf@brf@open	381
	K	\PackageInfo	\the 92, 95, 276, 291,	
\kvsetkeys	8 362, 402, 419	300, 303, 306,	
	L	\page@backref . . .	313, 330, 332, 333	
\let 22, 26, 29, 32, 89,		\par . 160, 165, 206, 208	\thebibliography . .	
161, 166, 185,		\ProcessKeyvalOptions 350, 351	
209, 212, 216,	 137	\thepage	407, 413
231, 233, 240,		\protect 228,	\toks	327, 332
244, 245, 251,		262, 272, 287, 308	\toks@ . . . 94, 95, 97,	
256, 309, 310,		\protected@write . .	298, 300, 303,	
325, 348, 349,	 405, 411	306, 313, 329, 330	
350, 356, 357, 392		\protected@xdef . . .	\tw@	327, 332
\long . 16, 17, 18, 19, 246		. 227, 260, 265, 280		
	M	\providecommand 190, 191	X	
\makeatletter	372	R	\x 101, 110, 219, 222,	
\MessageBreak	181	\relax . 88, 102, 226,	223, 225, 226,	
	N	256, 274, 289, 380	227, 231, 232,	
\newblock	187, 208	\RequirePackage 2, 3, 424	233, 234, 235,	
\newcommand	8	\RerunFileCheck . . .	236, 254, 260,	
\newif	148, 150	. . . 426	261, 265, 266,	
\newwrite	376	\reserved@a . . . 241, 250	267, 274, 276,	
\noexpand		\reserved@b . . . 247, 250	280, 281, 282,	
. 102, 104, 106,		S	289, 291, 328, 336	
		\section@backref 17, 26	\xdef	276, 291, 313
		\setbox	Z	
		254	\z@	321
		\SetupKeyvalOptions . 4		